SAFETY DATA SHEET

SDS Number: 205

COOGAR 98



SECTION 1: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION Product Identifier : COOGAR 98 Chemical Formula : O2 + Ar Refer to section 3 for REACH information Relevant identified uses of the substance or mixture and uses advised against Use of the substance/mixture : General Industrial and Professional use. Perform risk assessment prior to use. Restrictions on use : Not for consumer use Details of the supplier of the safety data sheet

| Physical address | : Air Products South Africa (Pty) Ltd. |
|---------------------|---|
| | Silver Stream Business Park, 1 st Floor, Building 3, |
| | 10 Muswell Road South, |
| | Bryanston, 2191 |
| Telephone | : +27 (0)11 570 5000 (Head Office) |
| | +27 (0)11 977 6444 (Customer Care Cylinders) |
| | 0800 023 298 (Engineering / Bulk Services) |
| Emergency telephone | e number (24h) : 0800 650 315 |

SECTION 2: HAZARDS IDENTIFICATION

Classification of the substance or mixture

Gases under pressure – Compressed gas. H280: Contains gas under pressure; may explode if heated

Label elements

Hazard pictogram/symbols



:

Warning

Hazard Statements:

H280: Contains gas under pressure; may explode if heated

Precautionary Statements:

Storage

: P403: Store in a well-ventilated area

Other hazards

High pressure gas. May increase respiration and heartrate. Can cause rapid suffocation. Self-contained breathing apparatus (SCBA) may be required. Use a back flow protection device in the piping. Use only equipment rated for cylinder pressure. Close valve after each use and when empty. Read and follow the Safety Data Sheet (SDS) before use.

Environmental Effects

Not harmful.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Substances

Mixtures

: Not applicable

| Components | EINECS/ELINCS Number | CAS Number | Concentration (Volume) |
|------------|-------------------------|------------|---------------------------|
| Oxygen | 231-956-9 | 7782-44-7 | <21% |
| Argon | 231-147-0 | 7440-37-1 | Balance |

| Components | Classification (CLP) | REACH Reg.# |
|------------|---|-------------|
| Oxygen | Ox. Gas 1; H270 Press. Gas (Comp.); H280 | *1 |
| Argon | Press. Gas (Comp.); H280 | *1 |

*1: Listed in Annex IV/V REACH, exempted from registration.

*2: Registration not required. Substance manufactured or imported < t/y

*3: Registration not required: substance manufactured or imported < 1 t/y for nonintermediate uses.

SAFETY DATA SHEET - Coogar 98

SDS Number: 205

Refer to section 16 for full text of each relevant hazard statement (H)

Concentration is nominal. For the exact product composition, please refer to Air Products product specifications.

SECTION 4: FIRST AID MEASURES

Description of first aid measures

| General advice | : | Move victim to uncontaminated area wearing self- contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped. | | |
|---|----------|---|--|--|
| Eye contact | : | In case of direct contact with eyes, seek medical advice. | | |
| Skin contact | : | Adverse effects not expected from this product. | | |
| Ingestion | : | Ingestion is not considered a potential route of exposure. | | |
| Inhalation | : | Move to fresh air. If breathing has stopped or is laboured, give assisted respirations. Supplemental oxygen may be indicated. If the heart has stopped, trained personnel should begin cardiopulmonary resuscitation immediately. In case of shortness of breath, give oxygen. | | |
| Most important symptoms and effects, both acute and delayed | | | | |
| Symptoms | : | Exposure to oxygen deficient atmosphere may cause the following symptoms: Dizziness. Salivation. Nausea. Vomiting. Loss of mobility/consciousness | | |
| Indication of any immediate r Treatment | ned : | lical attention and special treatment needed If exposed or concerned: Get medical attention/advice | | |

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing media

| Suitable extinguishing media | : | The product itself does not burn. Use extinguishing |
|------------------------------|---|---|
| | | media appropriate for surrounding fire. |

Extinguishing media which must not be used for safety reasons : Do not use water jet to extinguish.

Special hazards arising from the substance or mixture

Upon exposure to intense heat or flame, cylinder will vent rapidly and or rupture violently. Product is non-flammable and does not support combustion. Move away from container and cool with water from a protected position. Keep containers and surroundings cool with water spray.

| Advice for fire-fighters : \ i f c f f f |
|--|
|--|

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level. Evacuate personnel to safe areas. Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. Monitor oxygen level. Ventilate the area.

| Environmental precautions | : | Do not discharge into any place where its accumulation |
|---------------------------|---|---|
| | | could be dangerous. Prevent further leakage or spillage |
| | | if safe to do so. |

Methods and materials for containment and cleaning up : Ventilate the area.

Additional advice : If possible, stop flow of product. Increase ventilation to the release area and monitor oxygen level. If leak is from cylinder or cylinder valve, call the Air Products emergency telephone number. If the leak is in the user's system, close the cylinder valve, safely vent the pressure, and purge with an inert gas before attempting repairs.

Reference to other sections : For more information refer to Section 8 and 13.

SAFETY DATA SHEET – Coogar 98 SDS Number: 205

SECTION 7: HANDLING AND STORAGE

Precautions for safe handling

Cylinders should be stored up right with valve protection guard in place and firmly secured to prevent falling or being knocked over. Use equipment rated for cylinder pressure. Protect cylinders from physical damage; do not drag, roll, slide or drop. Do not allow storage area temperature to exceed 50°C. Only experienced and properly instructed persons should handle compressed gases/cryogenic liquids. Before using the product, determine its identity by reading the label. Know and understand the properties and hazards of the product before use. When doubt exists as to the correct handling procedure for a particular gas, contact the supplier. Do not remove or deface labels provided by the supplier for the identification of the cylinder contents. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Do not remove valve guards. Before connecting the container, check the complete gas system for suitability, particularly for pressure rating and materials. Before connecting the container for use, ensure that back feed from the system into the container is prevented. Ensure the complete gas system is compatible for pressure rating and materials of construction. Ensure the complete gas system has been checked for leaks before use. Employ suitable pressure regulating devices on all containers when the gas is being emitted to systems with lower pressure rating than that of the container. Never insert an object (e.g. spanner/wrench, screwdriver, pry bar, etc.) into valve openings. Doing so may damage valve, causing a leak.

Open valve slowly. If user experiences any difficulty operating cylinder valve discontinue use and contact supplier. Close container valve after each use and when empty, even if still connected to equipment. Never attempt to repair or modify container valves or safety relief devices. Damaged valves should be reported immediately to the supplier. Close valve after each use and when empty. Do not subject containers to abnormal mechanical shocks which may cause damage to their valve or safety devices. Never attempt to lift a cylinder by its valve guard. Do not use containers as rollers or supports or for any other purpose than to contain the gas as supplied. Never strike an arc on a compressed gas cylinder or make a cylinder a part of an electrical circuit. Do not smoke while handling product or cylinders. Never re-compress a gas or a gas mixture without first consulting the supplier. Never attempt to transfer gases from one cylinder/container to another. Always use backflow protective device in piping. Never use direct flame or electrical heating devices to raise the pressure of a container. Containers should not be subjected to temperatures above 50°C. Prolonged periods of cold temperature below -30°C should be avoided.

Conditions for safe storage, including any incompatibilities

Full containers should be stored so that oldest stock is used first. Containers should be stored in a purpose-built compound which should be well ventilated, preferably in the open air. Stored containers should be periodically checked for general condition and leakage. Observe all regulations and local requirements regarding storage of containers. Protect containers stored in the open against rusting and extremes of weather.

Containers should not be stored in conditions likely to encourage corrosion. Containers should be stored in the vertical position and properly secured to prevent toppling. The container valves should be tightly closed and where appropriate valve outlets should be capped or plugged. Container valve guards or caps should be in place. Keep containers tightly closed in a cool, well-ventilated place. Store containers in location free from fire risk and away from sources of heat and ignition. Full and empty cylinders should be segregated. Do not allow storage temperature to exceed 50°C. Return empty containers in a timely manner.

Technical measures/Precautions

Containers should be segregated in the storage area according to the various categories (e.g. flammable, toxic, etc.) and in accordance with local regulations. Keep away from combustible material

SECTION 8: EXPOSURE CONTROLS AND PERSONAL PROTECTION

Exposure controls

Engineering measures

Provide natural or mechanical ventilation to prevent oxygen deficient atmospheres below 19.5% oxygen.

Personal protective equipment

| Respiratory protection | pressure deficient | ained breathing apparatus (SCBA) or positive airline with mask are to be used in oxygen- atmosphere. Air purifying respirators will not rotection. Users of breathing apparatus must d. |
|--------------------------------|-----------------------|---|
| Hand protection | | rk gloves when handling cylinders. Standard Protective gloves against mechanical risk |
| | | kthrough time of the selected glove(s) must be nan the intended use period. |
| Eye/face protection | , , | asses recommended when handling cylinders. EN 166-Personal eye-protection. |
| Skin and body protection | cylinders | oes are recommended when handling . Standard EN ISO 20345- Personal protective nt-Safety footwear |
| Special instructions for prote | on and hygie | ene : Ensure adequate ventilation, especially in confined areas. |
| Remarks | Simple a | sphyxiant. |

SDS Number: 205

| nformation on basic physica | al a | nd chemical properties | R |
|--------------------------------|------|--|--------|
| Form | : | Compressed gas. | |
| Colour | : | Colourless gas | С |
| Odour | : | None. Mixture contains one or more component(s) which have the following odour: No odour warning properties. | P C |
| Molecular Weight | : | 39.86 g/mol | Ir |
| Relative vapour density | : | 1.38 (air = 1) Heavier than air. | н |
| Relative density | : | Not applicable | |
| Vapour pressure | : | No data available | |
| Density | : | 0.0017 g/cm ³ Note: (as vapour) | s |
| Specific Volume | : | 0.60 m ³ /kg | 3 |
| Melting/freezing point | : | No data available | h |
| Boiling point/range | : | -185.8 °C | L |
| Water solubility | : | Not known but considered to have low solubility. | |
| Partition coefficient n-octano | l/wa | ter [log Kow] : Not known | |
| рН | : | Not applicable | |
| Viscosity | : | No reliable data available | |
| Particle characteristics | : | Not applicable | |
| Upper and Lower explosion/f | lam | mability limits : Non flammable | |
| Flash point | : | Not applicable | |
| Auto-ignition temperature | : | Non flammable | |
| Decomposition temperature | : | Not applicable | |
| Other information | | | A |
| Explosive properties | : | Not applicable | |
| Oxidizing properties | : | Not applicable | |
| Odour threshold | : | Odour threshold is subjective and inadequate to warn of | |
| | | overexposure | |
| Evaporation rate | : | Not applicable | |
| Flammability (solid, gas) | : | Refer to production classification in Section 2 | |

ECTION 10: STABILITY AND REACTIVITY

| Reactivity | : | No reactivity hazard other than the effects described in the sub-sections below. |
|--------------------------------|------|---|
| Chemical Stability | : | Stable under normal conditions. |
| Possibility of hazardous reac | tion | ns : No data available |
| Conditions to avoid | : | None under recommended storage and handling conditions (Section 7) |
| ncompatible materials | : | No data available |
| Hazardous decomposition pr | odu | Under normal conditions of storage and use, hazardous decomposition products should not be produced. |
| SECTION 11: TOXICOLOGIC | AL I | NFORMATION |
| nformation on toxicological | effe | cts |
| Likely routes of exposure | | |
| Effects on Eye | : | In case of direct contact with eyes, seek medical advice |
| Effects on Skin | : | Adverse effects not expected from this product |
| Inhalation effects | : | In high concentrations may cause asphyxiation. Asphyxiation may bring about unconsciousness without warning and so rapidly that victim may be unable to protect themselves |
| Ingestion effects | : | Ingestion is not considered a potential route of exposure |
| Symptoms | : | Exposure to oxygen deficient atmosphere may cause the following symptoms: Dizziness. Salivation. Nausea. Vomiting. Loss of mobility/consciousness. |
| Acute toxicity | | |
| Acute oral toxicity | : | No data available on the product itself. |
| Acute inhalation toxicity | : | No data available on the product itself. |
| Acute dermal toxicity | : | No data available on the product itself |
| Skin corrosion/irritation | : | No data available |
| Serious eye damage / irritatio | n | : No data available |
| Sensitization | : | No data available |
| | | |

Note: Properties are nominal and may vary due to the composition of the gas mixture

SAFETY DATA SHEET – Coogar 98

SDS Number: 205

Chronic toxicity or effects from long term exposure

| Carcinogenicity | : No data available | | |
|------------------------------|---------------------------------|-----|-------------------|
| Reproductive toxicity | : No data available on the | pro | duct itself |
| Germ cell mutagenicity | : No data available on the | pro | duct itself |
| Specific target organ system | nic toxicity (single exposure) | : | No data available |
| Specific target organ system | nic toxicity (repeated exposure |) : | No data available |
| Aspiration hazard | : No data available | | |

SECTION 12: ECOLOGICAL INFORMATION

| Toxicity | | |
|-------------------------------|-----|--|
| Aquatic toxicity | : | No data is available on the product itself. |
| Toxicity to other organisms | : | No data is available on the product itself. |
| Persistence and degradability | y | |
| No data available | | |
| Bioaccumulative potential | : | Refer to section 9 "Partition Coefficient (n- octanol/water)". |
| Mobility in soil | : | Because of its high volatility, the product is unlikely to cause ground pollution. |
| Other adverse effects | | |
| This product has no known eo | co- | toxicological effects. |
| Effect on the ozone layer | : | No known effects from this product. |
| Ozone Depleting Potential | : | None |
| Effect on global warming | : | No known effects from this product. |

SECTION 13: DISPOSAL CONSIDERATIONS

Global Warming Potential : None

| Waste treatment method | : | Contact supplier if guidance is required. Return unused product in original cylinder to supplier. |
|------------------------|---|---|
| Contaminated packaging | : | Return cylinder to supplier. |

SECTION 14: TRANSPORT INFORMATION

| AUR |
|-----|
| |

| UN/ID No. Proper shipping name Class or Division Tunnel Code Label(s) ADR/RID Hazard ID no. Marine Pollutant | UN1956 COMPRESSED GAS, N.O.S. (Argon, Oxygen) 2 (E) 2.2 20 No |
|--|---|
| UN/ID No. | : UN1956 |
| Proper shipping name Class or Division Label(s) Marine Pollutant | Compressed gas, n.o.s. (Argon, Oxygen) 2.2 2.2 No |
| UN/ID No. | : UN1956 |
| Proper shipping name Class or Division Label(s) Marine Pollutant Segregation Group RID | COMPRESSED GAS, N.O.S. (Argon, Oxygen) 2.2 2.2 No None |
| UN/ID No. | : UN1956 |
| Proper shipping name Class or Division Label(s) Marine Pollutant | COMPRESSED GAS, N.O.S. (Argon, Oxygen) 2 2.2 No |

Further Information

Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Ensure compliance with applicable regulations.

Before transporting product containers ensure that they are firmly secured and cylinder valve is closed and not leaking, valve outlet cap nut or plug (where provided) is correctly fitted and valve protection device (where provided) is correctly fitted.

The transportation information is not intended to convey all specific regulatory data relating to this material. For complete transportation information, contact an Air Products customer service representative.

SECTION 15: REGULATORY INFORMATION

| : | Occupational Health and Safety Act 85 of 1993 (and Regulations) |
|---|--|
| : | Safety data sheet for chemical products- Content and order of sections |
| : | Globally Harmonized System of classification and labelling of chemicals (GHS) |
| : | The classification and labelling of dangerous substances and preparations for sale and handling |
| : | Transportable containers for compressed, dissolved and liquefied gases – Basic design, manufacture, use and maintenance |
| : | Transport of dangerous goods – Design, construction, testing, approval and maintenance of road vehicles and portable tanks |
| : | The identification and classification of dangerous goods for transport |
| : | Transport of dangerous goods – Packaging and large packaging for road and rail transport Part 1: Packaging / Part 2: Large Packaging |
| | : : : : |

SECTION 16: OTHER INFORMATION

Ensure all national/local regulations are observed.

Hazard Statement

H280: Contains gas under pressure, may explode if heated

Indication of Method

Gases under pressure. Compressed gas. Contains gas under pressure; may explode if heated.

Abbreviations and acronyms

ATE – Acute Toxicity Estimate

CLP – Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008

REACH – Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006

EINECS - European Inventory of Existing Commercial Chemical Substances

- ELINCS European List of Notified Chemical Substances
- CAS# Chemical Abstract Service number

| | PPE – Personal Protective Clothing |
|---|---|
| | Kow – octanol-water partition coefficient |
| | LC50- Lethal Concentration to 50% of a test population |
| | LD50 – Lethal Dose to 50% of a test population (Median Lethal Dose) |
| | OEL – Occupational Exposure Limit |
| | PBT – Persistent Bioaccummulative and Toxic |
| | vPvB - Very Persistent and Very Bioaccummulative |
| | STOT – Specific Target Organ Toxicity |
| | EN – European Standard |
| | UN – United Nations |
| | ADR – European Agreement concerning the International Carriage of Dangerous Goods by Road |
| | IATA – International Air Transport Association |
| | IMDG – International Maritime Dangerous Goods |
| | RID – Regulations concerning the International Carriage of Dangerous Goods by Rail |
| | |
| _ | |

Details given in this document are believed to be correct at the time of going to press. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

> (Reference <u>www.airproducts.com:</u> Air Products PLC M13ArO2 MSDS Number 30000002956 / Version 2.1 / Revision Date 24.03.2020)